




244GLE



244GLE. Technical specifications.

ENGINE	244 GLE
Designation	B 21 E
Displacement, cm ³	2127
Bore x stroke mm	92.0 x 80.0
Max. output hp at r/m DIN	123/5500
Max. output kW at r/s DIN	90/92
Max. Torque kpm at r/m DIN	17.3/3500
Max. torque Nm at r/s DIN	170/58
Compression ratio	9.3:1
Carburation	CI fuel injection
STANDARD EQUIPMENT¹⁾	244 GLE
AM/FM radio, stereo cassette	Yes
Instruments	Clock
Glazing	Tinted glazing (Not windscreen)
Outer rearview mirror	One
Upholstery	leather
Height adjustment, driving seat	By levers
Centre armrest in rear seat	Yes
Carpeting	Fully carpeted. Short pile
Boot lighting	Yes
Steering box ratio	17.3:1 Power assisted
Steering wheel turns, lock to lock	3.5
Rims	5.5 J 14" aluminium alloy
Steel braced radial ply tyres	185/70 HR 14"

¹⁾ The equipment listed above is additional to the items specified as standard in the text below.

Engine

Four-cylinder, water-cooled with five-bearing crankshaft. Overhead camshaft and cross-flow aluminium-alloy cylinder head.

Cooling system

Capacity 9.5 litres. Sealed.

Electrical system

12V/60Ah battery. 55A alternator.

Fuel tank

Capacity 60 litres. Safety location beside rear axle.

Transmission

Automatic: fully automatic.

Steering gear

Rack and pinion steering. Split steering column of safety type.

Suspension

Front: spring strut type incorporating coil springs and double-acting telescopic shock absorbers. Stabiliser. Rear: live rear axle carried by longitudinal control arms and torque rods. Lateral location by track rod. Coil springs and double-acting shock absorbers. Stabiliser.

Braking system

Self-adjusting disc brakes on all four wheels. Dual circuits, power-assisted, each operating simultaneously on both front wheels and on each of the rear wheels. Special alloy brake pipes. A relief valve in each circuit prevents the rear wheels from locking prematurely in emergency braking. Master cylinder of stepped-bore type. Handbrake operates independently on separate rear wheel drums.

Instrumentation and controls

Padded dashboard. Rheostat-controlled instrument lighting. Tachometer. Six-figure odometer with tripmeter, fuel gauge and coolant temperature gauge. Warning lamps for alternator charge, oil pressure, main beam, handbrake application and brake failure. Bulb integrity sensor. Audible and optical warning for turn indicators. Glovebox light. Combined steering wheel and ignition lock. Centre console carries controls for electrically heated rear window and four-way hazard warning lamps. "Fasten seat belts". Controls for air-conditioning, fog lights and electric antenna. Cigarette lighter. Ashtray.

Other standard equipment

Combined lever for turn indicators, main and dipped beams and main beam flasher. Combined stalk for two-speed and intermittent action windscreen wipers, and electric windscreen washer. Halogen headlights. Automatic daytime safety lights. Automatic reversing lights. Make-up mirror in glovebox. Head restraints on front seats. Inertia reel front seat belts. Two rear outer passengers have inertia reel belts, centre passenger has lap belt. Rear "Fasten seat belts" reminder. High-impact laminated windscreen. Padded sun visors. Day/night rearview mirror of safety type. Roof lining of fibreglass pressure moulding. Childproof rear door locks. Towing points front and rear. Mudflaps.

Turning circle diameter

Between kerbs9.8m

Boot capacity

Cargo area dimensions.....615dm³

Weights, approx. (244 GLE)

Kerbweight1340kg
Grossweight1780kg
Permissible trailer weight1500kg

Warranty

Twelve month warranty irrespective of kilometers.

The factory reserves the right to make changes at any time, without notice, to prices, colours, materials, equipment, specifications and models and also to discontinue models.

