



**VOLVO** 264



The Volvo 264 GL has leather or plush upholstery. All the interior trim is flame resistant.



The instrumentation includes a comprehensive system of warning and reminder lights.

	264 GL
<b>Engine</b>	
Designation	B27E
No. of cylinders	6
Displacement cm <sup>3</sup>	2664
Bore x stroke, mm	88.0 x 73.0
Max output hp at r/m DIN	140/6000
Max output kW at r/s DIN	103/100
Max torque kpm r/m DIN	20.8/3000
Max torque Nm at r/s DIN	204/50
Compression ratio	8.7:1
Carburation	CI fuel injection
<b>Other standard equipment<sup>1</sup></b>	
Headlight wipers/washers	Yes
Instrumentation	Clock. Tachometer
Steering wheel diameter	400 mm.
	Integral foam covered
Electrically powered windows	Front and rear side windows
Tinted glazing	Yes (not windscreen)
Make-up mirror	In glovebox
Upholstery	Leather or plush
Full carpeting	Deep pile
Air conditioning	Yes
Fixed head restraints	Front and rear
Oddments storage	In front doors and front seat backrests
Luggage compartment trim	Fully carpeted
Luggage compartment lighting	Yes
Rims	5.5J-14"
Steel braced radial ply tyres	185/70 HR 14

1) The equipment items listed in this table are additional to those specified in the text below.

#### Engine

Water-cooled V6 with aluminium-alloy block and cylinder heads. CI fuel delivery system. Contactless solid-state ignition system. Overhead camshafts and rocker arms.

#### Cooling system

Capacity 10.9 litres. Sealed.

#### Electrical system

12V/60Ah.55A alternator.

#### Transmission

The Volvo 264 GL has a three-stage automatic transmission with six illuminated positions.

#### Steering gear

Rack and pinion. Safety steering column of telescopic type. Ratio 17.1:1 power assisted. Number of turns lock to lock 3.5.

#### Suspension

Front: spring strut type with stabiliser. Rear: live, carried in rubber-mounted control arms and torque rods. Transverse location by track rod. Coil springs and telescopic shock absorbers with stabiliser.

#### Braking system

Power-assisted, all-disc. Dual circuit, triangle-split system. Each circuit

operates simultaneously on both front wheels and on each of the rear wheels. Brake pipes of rust-resistant copper and nickel alloy. Relief valves in each circuit prevent the rear wheels from locking up prematurely during emergency braking. Master cylinder of stepped-bore type. Handbrake operates on rear wheels through separate drums.

#### Instrumentation

Housed in padded dashboard. Rheostat-controlled instrument lighting. Six-figure mileometer with tripmeter, fuel gauge and coolant temperature gauge. Warning lamps for charging, oil pressure, main beam, turn indicators, handbrake and brake circuit failure. Bulb integrity sensor. Glovebox lighting. Combined steering and ignition lock. Centre console: switches for electrically heated rear window, four-way hazard warning lights, and "Fasten seat belts" reminder. Heating and ventilation controls. Cigar lighter and ashtray. Also controls for air conditioning, electrically operated windows in front doors and electric antenna. AM/FM radio/stereo cassette.

#### Other standard equipment

Combined stalk for turn indicators, main and dipped beam and headlight flasher. Combined stalk for two-speed windscreen wipers and electric windscreen washers. Rectangular, halogen headlights with separate reflectors for main and dipped beams. Automatic daytime safety lights. Automatic reversing lights. High-impact laminated windscreen. Padded sun visors. Day/night rearview mirror of safety type. Roof lining of moulded fibreglass. Inertia reel front and rear seat belts with static lap belt for centre rear passenger. Rear "Fasten seat belts" reminder. Towing points front and rear. Outer rearview mirror.

#### Exterior dimensions

Overall length	mm
Overall width	.4898
Overall height	.1707
Wheelbase	.1435
Turning circle diameter between kerbs	.2640
	.9.8m

#### Interior dimensions

Hip height	mm
Shoulder height	.1430
Front seat, max. depth	.470
Front seat, max. width	.560
Boot capacity	.615 dm <sup>3</sup>
With SAE cases	.395 dm <sup>3</sup>

#### Weights, approx.

Kerb weight	.1370 kg
Gross weight	.1840 kg
Trailer weight	.1500 kg

#### Warranty

Twelve-month warranty irrespective of mileage.

The factory reserves the right to make changes at any time, without notice, to prices, colours, materials, equipment, specifications and models and also to discontinue models.